




DG25C-B



"S"=7.62x(P-1)
"L"=7.62x(P-1)+9.12



极数	2	3	4	5	6	7	8	9	10	11	12	13	14	15
L(mm)	16.74	24.36	31.98	39.60	47.22	54.84	62.46	70.08	77.70	85.32	92.94	100.56	108.18	115.80
S(mm)	7.62	15.24	22.86	30.48	38.10	45.72	53.34	60.96	68.58	76.20	83.82	91.44	99.06	106.68
极数	16	17	18	19	20	21	22	23	24	25	26	27	28	
L(mm)	123.42	131.04	138.66	146.28	153.90	161.52	169.14	176.76	184.38	192.00	199.62			
S(mm)	114.30	121.92	129.54	137.16	144.78	152.40	160.02	167.64	175.26	182.88	190.50			

螺丝



UL

IEC

300V

250V

15A

24A

24-14AWG

2.5mm²

AC2000V/1 Min

500M Ω /DC500V

0.5N.m 4.4Lb.in

-40℃~+105℃

7.62mm(.300")

2P-26P

PA66.UL94V-0









黄铜 0.8厚 镀锡

钢 M3镀镍

订购方式：

DG25 — — **P** — **1** —



X	X	X
客户需求		

C:   S:  
H:   R:  

A	有固定孔
B	无固定孔

极数

颜色	1	灰色	4	绿色
	3	黑色		



THROANGLE PROJECTION



寧波高正電子有限公司
DEGSON ELECTRONICS CO.,LTD.

NAME

DG25C-B